



# SAFETY DATA SHEET

## 1. Product and Company Identification

<b>PRODUCT NUMBER:</b>	1733	<b>COMPANY PHONE:</b>	1-800-241-8180
<b>PRODUCT NAME:</b>	LIKE NU	<b>EMERGENCY TELEPHONE:</b>	1-800-241-8180
<b>PRODUCT DESCRIPTION:</b>	Aerosol Acoustical Ceiling Tile Restorer	<b>INFOTRAC:</b>	1-800-535-5053
<b>COMPANY INFORMATION:</b>	<b>PRO CHEM, INC.</b> 1475 Bluegrass Lakes Parkway Alpharetta, GA 30004		

## 2. Hazards Identification

<b>GHS CLASSIFICATION:</b> Flammable aerosols: Category 1 Serious eye damage/eye irritation: Category 2A Germ cell mutagenicity: Category 1B Carcinogenicity: Category 2 Reproductive toxicity (the unborn child): Category 2 Specific target organ toxicity, repeated exposure: Category 2 <b>OSHA defined hazards:</b> Not classified.	<b>SIGNAL WORD:</b> <b>DANGER</b>	<b>SYMBOL:</b>			
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------	----------------	-------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------

### HAZARD STATEMENTS:

Extremely flammable aerosol. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

### PRECAUTIONARY STATEMENTS:

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF EXPOSED OR CONCERNED: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

**Storage:** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

### ENVIRONMENTAL HAZARDS:

Hazardous to the aquatic environment, acute hazard: Category 3

Hazardous to the aquatic environment, long-term hazard: Category 3

### HAZARDS NOT OTHERWISE SPECIFIED:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

### SUPPLEMENTAL INFORMATION:

None.

## 3. Composition / Information on Ingredients

Chemical Name	CAS	Concentration % by Weight
Butane	106-97-8	20-40
Ethyl Alcohol	64-17-5	20-40
Acetone	67-64-1	10-20
Magnesium Silicate	14807-96-6	10-20
Propane	74-98-6	2.5-10
Titanium dioxide	13463-67-7	2.5-10
Toluene	108-88-3	2.5-10
Other components below reportable levels		10-20

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First Aid Measures

### EMERGENCY OVERVIEW

**GENERAL:** IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**SKIN:** Wash off with soap and water. Get medical attention if irritation develops and persists.

### INHALATION:

Move to fresh air. Call a physician if symptoms develop or persist.

### INGESTION:

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

### MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Prolonged exposure may cause chronic effects.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:**  
 Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**5. Fire Fighting Measures**

**SUITABLE FIRE EXTINGUISHING MEDIA:**  
 Alcohol resistant foam. Powder. Carbon dioxide (CO<sub>2</sub>).

**UNSUITABLE FIRE EXTINGUISHING MEDIA:**  
 Do not use water jet as an extinguisher, as this will spread the fire.

**SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:**  
 Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

**SPECIFIC FIRE-FIGHTING METHODS:**  
 Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:**  
 Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**GENERAL FIRE HAZARDS:**  
 Extremely flammable aerosol.

**6. Accidental Release Measures**

**PERSONAL PRECAUTIONS:**  
 Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during cleanup. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

**MATERIALS AND METHODS FOR CLEANUP:**  
 Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see Section 13 of the SDS.

**ENVIRONMENTAL PRECAUTIONS:**  
 Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, watercourses or onto the ground.

**7. Handling and Storage**

**SAFE HANDLING:**  
 Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not reuse empty containers. Do not breathe gas. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

**SAFE STORAGE & INCOMPATIBILITIES:**  
 Level 2 Aerosol.  
 Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure Controls / Personal Protection**

**Occupational exposure limits**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

COMPONENTS	TYPE	VALUE	FORM
Acetone (CAS 67-64-1)	PEL	2400 mg/m <sup>3</sup> 1000 ppm	
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m <sup>3</sup> 1000 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m <sup>3</sup> 1000 ppm	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m <sup>3</sup>	Total dust.

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

COMPONENTS	TYPE	VALUE	FORM
Toluene (CAS 108-88-3)	Ceiling	300 ppm	
	TWA	200 ppm	

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

COMPONENTS	TYPE	VALUE	FORM
Magnesium Silicate (CAS 14807-96-6)	TWA	0.3 mg/m <sup>3</sup>	Total dust.
		0.1 mg/m <sup>3</sup>	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values				
COMPONENTS	TYPE	VALUE	FORM	
Acetone (CAS 67-64-1)	STEL	500 ppm		
	TWA	250 ppm		
Butane (CAS 106-97-8)	STEL	1000 ppm		
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm		
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable fraction.	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>		
Toluene (CAS 108-88-3)	TWA	20 ppm		
US. NIOSH: Pocket Guide to Chemical Hazards				
COMPONENTS	TYPE	VALUE	FORM	
Acetone (CAS 67-64-1)	TWA	590 mg/m <sup>3</sup>		
		250 ppm		
Butane (CAS 106-97-8)	TWA	1900 mg/m <sup>3</sup>		
		800 ppm		
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m <sup>3</sup>		
		1000 ppm		
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m <sup>3</sup>	Respirable.	
Propane (CAS 74-98-6)	TWA	1800 mg/m <sup>3</sup>		
		1000 ppm		
Toluene (CAS 108-88-3)	STEL	560 mg/m <sup>3</sup>		
		150 ppm		
	TWA	375 mg/m <sup>3</sup>		
		100 ppm		
BIOLOGICAL LIMIT VALUE:				
ACGIH Biological Exposure Indices:				
Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in Urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
* - For sampling details, please see the source document.				
EXPOSURE GUIDELINES:				
<b>US - California OELs: Skin designation:</b>				
Toluene (CAS 108-88-3):		Can be absorbed through the skin.		
<b>US - Minnesota Haz Subs: Skin designation applies:</b>				
Toluene (CAS 108-88-3):		Skin designation applies.		
APPROPRIATE ENGINEERING CONTROLS:				
Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.				
INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:				
				
<b>Eye Protection:</b> Wear safety glasses with side shields (or goggles).				
<b>Skin Protection:</b> Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Wear suitable protective clothing. Use of an impervious apron is recommended.				
<b>Respiratory Protection:</b> If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.				
<b>Thermal Hazards:</b> Wear appropriate thermal protective clothing, when necessary.				
<b>General Hygiene Considerations:</b> Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.				

9. Physical & Chemical Properties			
Physical State:	Gas.	Flammability (solid/gas):	Not available.
Form:	Aerosol.	Flammability Limit-lower (%):	3.4% estimated.
Color:	Not available.	Flammability Limit-upper (%):	10.7% estimated.
Odor:	Not available.	Explosive Limit – lower (%):	Not available.
Odor Threshold:	Not available.	Explosive Limit – upper (%):	Not available.
pH:	Not available.	Vapor Pressure:	95.21 psig @70°F estimated.
Melting/Freezing Point:	Not available.	Vapor Density:	Not available.
Initial Boiling Point/Range:	179.76 °F (82.09 °C) estimated.	Relative Density:	Not available.
Partition Coeff (n-octanol/water):	Not available.	Solubility (water):	Not available.
Viscosity:	Not available.	Auto-Ignition Temperature:	699.8°F (371°C) estimated.
Specific Gravity:	0.988 estimated.	Decomposition Temperature:	Not available.
Flash Point:	-156.0 °F (-104.4 °C) Propellant estimated.	Evaporation Rate:	Not available.
Explosive Properties:	Not explosive.	Oxidizing Properties:	Not oxidizing.

## 10. Stability & Reactivity Information

### REACTIVITY:

The product is stable and non-reactive under normal conditions of use, storage and transport.

### CHEMICAL STABILITY:

Material is stable under normal conditions.

### POSSIBILITY OF HAZARDOUS REACTIONS:

Hazardous polymerization does not occur.

### INCOMPATIBLE MATERIALS:

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

### CONDITIONS TO AVOID:

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

### HAZARDOUS DECOMPOSITION PRODUCTS:

No hazardous decomposition products are known.

## 11. Toxicological Information

### PRIMARY ROUTE OF ENTRY:

**Eyes:** Causes serious eye irritation.

**Skin:** No adverse effects due to skin contact are expected.

**Inhalation:** May cause damage to organs through prolonged or repeated exposure by inhalation.

**Ingestion:** Expected to be a low ingestion hazard.

### SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

### ACUTE TOXICITY:

COMPONENTS	SPECIES	TEST RESULTS
<hr/>		
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
	Rabbit	> 9.4 ml/kg, 24 Hours
		> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
<i>Oral</i>		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
<hr/>		
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
<hr/>		
Ethyl Alcohol (CAS 64-17-5)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
<i>Oral</i>		
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Pig	> 5000 mg/kg
	Rat	10470 mg/kg
		7800 ml/kg
<hr/>		
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
<hr/>		
Titanium dioxide (CAS 13463-67-7)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 2.28 mg/l, 4 Hours
<i>Oral</i>		
LD50	Mouse	> 5000 mg/kg
	Rat	> 2000 mg/kg

Toluene (CAS 108-88-3)

**Acute**

*Dermal*

LD50

Rabbit > 5000 mg/kg, 24 Hours

*Inhalation*

LC50

Mouse 6405 - 7436 ppm, 6 Hours

5320 ppm, 8 Hours

Rat 5879 - 6281 ppm, 6 Hours

25.7 mg/l, 4 Hours

*Oral*

LD50

Rat > 5000 mg/kg

\*Estimates for product may be based on additional component data not shown.

**SKIN CORROSION/IRRITATION:**

Not applicable.

**SERIOUS EYE DAMAGE/IRRITATION:**

Causes serious eye irritation.

**RESPIRATORY SENSITIZATION:**

Not a respiratory sensitizer.

**SKIN SENSITIZATION:**

This product is not expected to cause skin sensitization.

**GERM CELL MUTAGENICITY:**

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**CARCINOGENICITY:**

Suspected of causing cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity:**

Magnesium Silicate (CAS 14807-96-6): 2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7): 2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3): 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens:** Not listed.

**REPRODUCTIVE TOXICITY:**

Suspected of damaging the unborn child.

**SPECIFIC TARGET ORGAN TOXICITY (single exposure):**

Not classified.

**SPECIFIC TARGET ORGAN TOXICITY (repeated exposures):**

May cause damage to organs through prolonged or repeated exposure.

**ASPIRATION HAZARD:**

Not likely, due to the form of the product.

**CHRONIC EFFECTS:**

May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

**12. Ecological Information**

**ECOTOXICITY:**

Harmful to aquatic life with long lasting effects.

**COMPONENTS**

**SPECIES**

**TEST RESULTS**

Acetone (CAS 67-64-1)

**Aquatic**

Crustacea

EC50

Water flea (Daphnia magna)

21.6 - 23.9 mg/l, 48 hours

Fish

LC50

Rainbow trout, donaldson trout (Oncorhynchus mykiss)

4740 - 6330 mg/l, 96 hours

Ethyl Alcohol (CAS 64-17-5)

**Aquatic**

Crustacea

EC50

Water flea (Daphnia magna)

7700 - 11200 mg/l, 48 hours

Fish

LC50

Fathead minnow (Pimephales promelas)

> 100.1 mg/l, 96 hours

Titanium dioxide (CAS 13463-67-7)

**Aquatic**

Crustacea

EC50

Water flea (Daphnia magna)

> 1000 mg/l, 48 hours

Fish

LC50

Mummichog (Fundulus heteroclitus)

> 1000 mg/l, 96 hours

Toluene (CAS 108-88-3)

**Aquatic**

Algae

IC50

Algae

433.0001 mg/L, 72 Hours

Crustacea

EC50

Daphnia

7.645 mg/L, 48 Hours

Fish

LC50

Water flea (Daphnia magna)

5.46 - 9.83 mg/l, 48 hours

Fish

LC50

Coho salmon, silver salmon (Oncorhynchus kisutch)

8.11 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**PERSISTENCE AND DEGRADABILITY:**

No data is available on the degradability of this product.

**BIOACCUMULATIVE POTENTIAL:**

**Partition coefficient n-octanol / water (log Kow)**

Acetone

-0.24

Butane

2.89

Ethyl Alcohol

-0.31

Propane

2.36

Toluene

2.73

**MOBILITY IN SOIL:**

No data available.

**OTHER ADVERSE EFFECTS:**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal Consideration****DISPOSAL INSTRUCTIONS:**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**LOCAL DISPOSAL REGULATIONS:**

Dispose in accordance with all applicable regulations.

**HAZARDOUS WASTE CODE:**

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**WASTE FROM RESIDUES/UNUSED PRODUCTS:**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**CONTAMINATED PACKAGING:**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste-handling site for recycling or disposal. Do not reuse empty containers.

**14. Transportation Information**

**DOT:** **UN Number:** UN1950  
**UN Proper Shipping Name:** Aerosols, flammable, (each not exceeding 1 L capacity)  
**Transport Hazard Class(es)**  
**Class:** 2.1  
**Subsidiary Risk:** -  
**Label(s):** 2.1

**Packing Group:** Not applicable.**Special Precautions for User:** Read safety instructions, SDS and emergency procedures before handling.**Special Provisions:** N82**Packaging Exceptions:** 306**Packaging Nonbulk:** None.**Packaging Bulk:** None.

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA:** **UN Number:** UN1950  
**UN Proper Shipping Name:** Aerosols, flammable  
**Transport Hazard Class(es)**  
**Class:** 2.1  
**Subsidiary Risk:** -  
**Label(s):** 2.1

**Packing Group:** Not applicable.**Environmental Hazards:** No.**ERG Code:** 10L**Special Precautions for User:** Read safety instructions, SDS and emergency procedures before handling.**Other Information:****Passenger and Cargo Aircraft:** Allowed with restrictions.**Cargo Aircraft Only:** Allowed with restrictions.**Packaging Exceptions:** LTD QTY

**IMDG:** **UN NUMBER:** UN1950  
**UN Proper Shipping Name:** AEROSOLS  
**Transport Hazard Class(es)**  
**Class:** 2.1  
**Subsidiary Risk:** -  
**Label(s):** 2.1

**Packing Group:** Not applicable.**Environmental Hazards:****Marine pollutant:** No.**EmS:** F-D, S-U**Special Precautions for User:** Read safety instructions, SDS and emergency procedures before handling.**Packaging Exceptions:** LTD QTY**TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 and the IBC CODE:**

Not applicable.

## 15. Regulatory Information

### US FEDERAL REGULATIONS:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D):** Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

Acetone (CAS 67-64-1) Listed.

Toluene (CAS 108-88-3) Listed.

**SARA 304 Emergency release notification:** Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not regulated.

### SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT of 1986 (SARA):

**Hazard categories:** Immediate Hazard – Yes.

Delayed Hazard – Yes.

Fire Hazard – Yes.

Pressure Hazard – No.

Reactivity Hazard – No.

**SARA 302 Extremely hazardous substance:** Not listed.

**SARA 311/312 Hazardous Chemical:** No.

**SARA 313 (TRI reporting):**

Chemical Name	CAS Number	% by Weight
Toluene	108-88-3	2.5-10

### OTHER FEDERAL REGULATIONS

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List:**

Toluene (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA):** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)):**

Acetone (CAS 67-64-1) 35% WV

Toluene (CAS 108-88-3) 35% WV

**DEA Exempt Chemical Mixtures Code Number**

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 594

### US STATE REGULATIONS

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100):** Not listed.

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)):**

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Magnesium Silicate (CAS 14807-96-6)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

**US. Massachusetts RTK - Substance List:**

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Ethyl Alcohol (CAS 64-17-5)

Magnesium Silicate (CAS 14807-96-6)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

**US. New Jersey Worker and Community Right-to-Know Act**

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Ethyl Alcohol (CAS 64-17-5)

Magnesium Silicate (CAS 14807-96-6)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Ethyl Alcohol (CAS 64-17-5)

Magnesium Silicate (CAS 14807-96-6)

Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

**US. Rhode Island RTK**

Acetone (CAS 67-64-1)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

**US. California Proposition 65:** WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

Toluene (CAS 108-88-3) Listed: January 1, 1991

**INTERNATIONAL INVENTORIES:**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other Information****DISCLAIMER:**

To the best of our knowledge, information contained herein is accurate. However, there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard, which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product, which may not be covered by this SDS. The user is responsible for full compliance.