



SAFETY DATA SHEET

1. Identification

Product identifier Motor Medic Universal Power Steering Fluid with Stop Leak

Other means of identification

SDS number M2713
Part No. M2713, M2732, M2734, M2713ES, M2734ES
Tariff code 3819.00.0090

Recommended use Power Steering Fluid

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name RSC Chemical Solutions
Address 600 Radiator Road
Indian Trail, NC 28079
United States

Telephone Customer Service: (704) 821-7643
Technical: (704) 684-1811

Website www.rscbrands.com

E-mail sds@rscbrands.com

Emergency phone number Emergency Telephone: (303) 623-5716
Emergency Contact: RMPDC (877) 740-5015

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid release to the environment.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information 86.75% of the mixture consists of component(s) of unknown acute dermal toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), Hydrotreated Heavy Naphthenic		64742-52-5	80 - < 90
Solvent Naphtha (petroleum), Light Arom.		64742-95-6	1 - < 3
Trimethylbenzene		25551-13-7	< 1
1,2,4-Trimethylbenzene		95-63-6	< 0.3
Kerosene (petroleum) Hydrodesulfurized		64742-81-0	< 0.3
1,2,3-trimethylbenzene		526-73-8	< 0.2
Mesitylene; (1,3,5-trimethylbenzene)		108-67-8	< 0.2
BENZENE, DIMETHYL		1330-20-7	< 0.1
BENZENE,1-METHYLETHYL-		98-82-8	< 0.1
NAPHTHALENE		91-20-3	< 0.1
Other components below reportable levels			10 - < 20

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Prevent product from entering drains. Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
BENZENE, DIMETHYL (CAS 1330-20-7)	PEL	435 mg/m3	
BENZENE,1-METHYLETHY L- (CAS 98-82-8)	PEL	100 ppm 245 mg/m3	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	PEL	50 ppm 5 mg/m3	Mist.
NAPHTHALENE (CAS 91-20-3)	PEL	2000 mg/m3 500 ppm 50 mg/m3	
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)	PEL	10 ppm 400 mg/m3	
		100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,3-trimethylbenzene (CAS 526-73-8)	TWA	25 ppm	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
BENZENE, DIMETHYL (CAS 1330-20-7)	STEL	150 ppm	
BENZENE,1-METHYLETHY L- (CAS 98-82-8)	TWA TWA	100 ppm 50 ppm	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)	TWA	200 mg/m3	Non-aerosol.
Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)	TWA	25 ppm	
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	
Trimethylbenzene (CAS 25551-13-7)	TWA	25 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1,2,3-trimethylbenzene (CAS 526-73-8)	TWA	125 mg/m3	
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm 125 mg/m3	
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	TWA	25 ppm 245 mg/m3	
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)	Ceiling	50 ppm 1800 mg/m3	
Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)	STEL TWA	10 mg/m3 100 mg/m3	Mist.
Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)	TWA	125 mg/m3	
NAPHTHALENE (CAS 91-20-3)	STEL	25 ppm 75 mg/m3	
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)	TWA	15 ppm 50 mg/m3 10 ppm 400 mg/m3	
		100 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
BENZENE, DIMETHYL (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.
NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0) Can be absorbed through the skin.
NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) or a face shield. Face shield is recommended.

Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear suitable protective clothing.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded. Dust mask.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Liquid Clear.
Physical state	Liquid.
Form	Liquid.
Color	Yellow.
Odor	Naphthenic
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-20 °F (-28.89 °C) estimated
Initial boiling point and boiling range	500 °F (260 °C) estimated
Flash point	> 205.0 °F (> 96.1 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	600 °F (315.56 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.42 lbs/gal
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.
Percent volatile	0.04 % estimated
Refractive index	1.49
Specific gravity	0.89
VOC	0.04 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
BENZENE, DIMETHYL (CAS 1330-20-7)		
Acute		
Oral		
LD50	Rat	3523 - 8600 mg/kg
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
Acute		
Oral		
LD50	Rat	1400 mg/kg
NAPHTHALENE (CAS 91-20-3)		
Acute		
Dermal		
LD50	Rabbit	> 2 g/kg
Oral		
LD50	Rat	490 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE, DIMETHYL (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.
 BENZENE,1-METHYLETHYL- (CAS 98-82-8) 2B Possibly carcinogenic to humans.
 NAPHTHALENE (CAS 91-20-3) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Reasonably Anticipated to be a Human Carcinogen.
 NAPHTHALENE (CAS 91-20-3) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.19 - 8.28 mg/l, 96 hours
BENZENE, DIMETHYL (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 7.711 - 9.591 mg/l, 96 hours
BENZENE,1-METHYLETHYL- (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (<i>Artemia</i> sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 2.7 mg/l, 96 hours
Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)		
Aquatic		
Fish	LC50	Goldfish (<i>Carassius auratus</i>) 9.89 - 15.05 mg/l, 96 hours
NAPHTHALENE (CAS 91-20-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (<i>Oncorhynchus gorbuscha</i>) 1.11 - 1.68 mg/l, 96 hours
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia pulex</i>) 2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>) 8.8 mg/l, 96 hours
		8.8 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

BENZENE, DIMETHYL 3.12 - 3.2
 BENZENE,1-METHYLETHYL- 3.66
 NAPHTHALENE 3.3

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number Not available.

UN proper shipping name Consumer commodity, MARINE POLLUTANT (RMM27HCOMPB Power Steering Comp, Solvent Naphtha (Petroleum) Light Aromatic)

Transport hazard class(es)

Class ORM-D

Subsidiary risk -

Label(s) None

Packing group Not available.

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 156, 306

Packaging non bulk 156, 306

Packaging bulk None

IATA

UN number UN3082

UN proper shipping name Environmentally Hazardous Substance, Liquid, N.O.S.

Transport hazard class(es)

Class 9

Subsidiary risk -

Label(s) 9

Packing group Not available.

Environmental hazards Yes

ERG Code 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates (petroleum), Hydrotreated Heavy Naphthenic), MARINE POLLUTANT (Solvent Naphtha (Petroleum) Light Aromatic)

Transport hazard class(es)

Class 9

Subsidiary risk -

Packing group III

Environmental hazards

Marine pollutant Yes

EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.


Solvent Naphtha (Petroleum) Light Aromatic
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE, DIMETHYL (CAS 1330-20-7)	Listed.
BENZENE, 1-METHYLETHYL- (CAS 98-82-8)	Listed.
NAPHTHALENE (CAS 91-20-3)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
NAPHTHALENE	91-20-3	< 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, 1-METHYLETHYL- (CAS 98-82-8)
NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**BENZENE,1-METHYLETHYL- (CAS 98-82-8) Listed: April 6, 2010
NAPHTHALENE (CAS 91-20-3) Listed: April 19, 2002**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**1,2,4-Trimethylbenzene (CAS 95-63-6)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE,1-METHYLETHYL- (CAS 98-82-8)
Distillates (petroleum), Hydrotreated Heavy Naphthenic (CAS 64742-52-5)
Kerosene (petroleum) Hydrodesulfurized (CAS 64742-81-0)
Mesitylene; (1,3,5-trimethylbenzene) (CAS 108-67-8)
NAPHTHALENE (CAS 91-20-3)
Solvent Naphtha (petroleum), Light Arom. (CAS 64742-95-6)**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-19-2015
Revision date	05-23-2017
Version #	05
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 0 Instability: 0

NFPA ratings**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

